

# ***NEWTON SUPPLY COMPANY INC.***

13953 SW 140 STREET MIAMI, FL. 33186 (305) 235-6503 1-800-888-2467 FAX (305) 235-7475 E-MAIL: nsc@netrus.net

## **EPO-GRIP ADHESIVE PASTE FILLER**

### DESCRIPTION:

A specially formulated two component paste consisting of 100% epoxy solids and bonding agents. Being neutral in color, this filler has the same appearance as the plastics used in the manufacture of new furniture and can easily be tinted to colors of choice.

Epo-Grip Paste Filler is easily mixed and initial curing occurs in less than 10 minutes at 77 degrees F. This filler sands, drills, and taps within a 1 hour period, and is an excellent material for securing and embedding bolts, screws and other devices. It will bond to wood, metal, phenolic plastics, glass and glass fabric, forestry products and ceramics. When used as a pouring resin, it produces smooth, accurate casts in minutes.

### SURFACE PREPARATION:

Surfaces must be free and clean of dirt, grease, oil, wax, moisture and loose particles. Rust, paint or surface oxidation must be removed prior to application.

### APPLICATION:

Mix thoroughly equal parts by volume of components "A" and "B" until a uniform color and consistency is obtained. Working time of a 100 gram mass at 77 degrees F is approximately 4 minutes, and initial curing occurs within 6 to 10 minutes. Curing at room temperature for 1 to 2 hours is usually sufficient for quick service, although 24 hours is recommended for near optimum properties. For best results, tinting colors should be introduced by equal volume into both components "A" and "B" prior to mixing.

### GENERAL:

Epo-Grip Paste Filler is designed as a general purpose rapid set filler. Based on reliable testing and evaluation, this product will bond to most substances and do a satisfactory job. However, due to the wide range of applications, and the varied conditions under which these applications are accomplished, there can be no assurance that this product will always provide 100% results. However, adherence to proper surface preparation, mixing, application and curing instructions should provide outstanding results.

### CAUTION:

Epo-Grip Paste Filler may cause skin or eye irritation. If contact occurs, wash skin immediately with soap and water: flush eyes immediately with water. Not to be taken internally. **KEEP OUT OF REACH OF CHILDREN!**

NOTE: Application of material is not recommended if ambient temperature is below 50 degrees F.

WARRANTIES: Newton Supply Company, Inc. guarantees our products conform to Newton Supply Co. Inc. quality control. Liability, if any, is limited to replacement of products. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY THE SELLER, EXPRESSED OR IMPLIED, STATUTORY BY OPERATION OR LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

***CHEMICALS    PAINT COATINGS    ADHESIVES    SEALANTS***