

# ***NEWTON SUPPLY COMPANY INC.***

13953 SW 140 STREET MIAMI, FL. 33186 (305) 235-6503 1-800-888-2467 FAX (305) 235-7475 E-MAIL : nsc@netrus.net

## **EPO-GRIP Seam and Repair Putty**

### DESCRIPTION:

Epo-Grip Seam and Repair Putty a two component putty consisting of 100% epoxy solids and bodying agents. It is easily mixed and enables low temperature bonding and repairing where high adhesion and low shrinkage are required.

Epo-Grip Seam and Repair Putty is a smooth high tack putty used for filling seams and making repairs in taxidermy applications. Can be easily colored using dry coloring tints and smoothes out well with water. Seam and Repair Putty can be sculpted with its non-sag consistency. Excellent for fish seams, fish mouth work, jaw sets, and many repair applications.

### SURFACE PREPARATION:

Surfaces must be free and clean of dirt, grease, oil, waxes, moisture and loose particles. Rust, paint or surface oxidation must be removed prior to application. For critical metal surfaces, a sandblast finish is recommended.

### APPLICATION:

Mix thoroughly equal parts by volume of components "A" and "B" until a uniform color and consistency is obtained. Working time of a 100 gram mass at 77 degrees F is approximately 20 minutes and initial cure occurs within 3 to 4 hours at room temperature. Average cure normally requires 24 hours, at which optimum properties are achieved. The larger the mass of adhesive used, the faster the cure. However, the opposite effect is obtained where less mass or a thinner film is applied. In this event, curing may take in excess of 24 hours. The use of heat will accelerate curing.

### CAUTION:

Epoxies can cause skin sensitization or other allergic responses. Avoid contact with eyes and skin. Use adequate ventilation. In case of skin contact, wash thoroughly with soap and water; for eyes, flush immediately with plenty of water for 15 minutes and get medical attention. After cure, epoxy is inert and safe to touch. **KEEP OUT OF REACH OF CHILDREN!**

NOTE: Application of material is not recommended if ambient temperature is below 50 degrees F.

WARRANTIES: Newton Supply Company, Inc. guarantees our products conform to Newton Supply Co. Inc. quality control. Liability, if any, is limited to replacement of products. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY THE SELLER, EXPRESSED OR IMPLIED, STATUTORY BY OPERATION OR LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

***CHEMICALS    PAINT COATINGS    ADHESIVES    SEALANTS***