

NEWTON SUPPLY COMPANY INC.

13953 SW 140 STREET MIAMI, FL. 33186 (305) 235-6503 1-800-888-2467 FAX (305) 235-7475 E-MAIL: nsc@netrus.net

EPO-GRIP ADHESIVE CLEAR PASTE (FAST SET)

DESCRIPTION:

A clear, two component, fast setting, epoxy paste adhesive which is easily mixed and where initial cure occurs in less than 10 minutes at 77 degrees F. Since it contains no solvents, there is no shrinkage; this allows for use where high performance structural bonding is required. Can be shaped and formed with a sharp cutting tool in 15 minutes and finish sanded in approximately 30 minutes. This paste adhesive develops strong, tough bonds to wood, metals, most plastics, epoxy laminates, glass and glass fabrics, forestry products, ceramics, masonry, marble and other construction materials. Excellent for use in the furniture repair trades where fast curing is required without sacrificing adhesion.

SURFACE PREPARATION:

Surfaces must be free and clean of dirt, grease, oil, wax, mold release coatings and loose particles.

APPLICATION:

Mix thoroughly equal parts by volume of components "A" and "B" until a smooth consistency is obtained. Working time of a one ounce mass at 77 degrees F is approximately 4 minutes and initial cure occurs within 6 to 10 minutes. Curing at room temperature for 1 to 2 hours is usually sufficient for quick service, although 24 hours is required for optimum properties. For best results, tinting powders should be introduced to both components "A" and "B" prior to mixing.

GENERAL:

Based on reliable testing and evaluation, this product will bond to most substances and do a satisfactory job. However, due to the wide range of applications and the varied conditions under which these applications are accomplished, there can be no assurance that this product will always provide 100% results. With proper consideration to surface preparation, mixing, application and curing, this product should provide outstanding results.

CAUTION:

Epoxies may cause skin or eye irritation. If contact occurs, wash skin immediately with soap and water; flush eyes immediately with copious amounts of water. Not to be taken internally. **KEEP OUT OF REACH OF CHILDREN!**

NOTE: Application of material is not recommended if ambient temperature is below 50 degrees F.

WARRANTIES: Newton Supply Company, Inc. guarantees our products conform to Newton Supply Co. Inc. quality control. Liability, if any, is limited to replacement of products. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY THE SELLER, EXPRESSED OR IMPLIED, STATUTORY BY OPERATION OR LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

CHEMICALS PAINT COATINGS ADHESIVES SEALANTS